



CHARGED WITH
R-454B
REFRIGERANT



SINGLE ZONE



OLYMPUS

E STAR®



ASCEND TO COMFORT
PEAK PERFORMANCE
HEATING & COOLING

Eligible for
**MRCOOL®
CAREPROGRAM**

JUST ASK
amazon alexa
works with the
Google Assistant



SMART HVAC
CONTROLLER®

SCAN HERE >
for the most up-to-date
version of this brochure.




Version Date: 12-03-2025

www.mrcool.com

The MRCOOL® Olympus E Star® Series: Ascend to Perfect Comfort

When your space needs powerful, dedicated heating or cooling, nothing else measures up. The MRCOOL® Olympus E Star® series is engineered to provide precise, year-round comfort in any space up to 1050 square feet—from garages and workshops to new additions and sun rooms.

Experience a level of performance that's truly Olympian, all while saving money and energy.



- Energy Saving
- Precise Temperature Control
- 1%-100% Fan Speed Setting
- Stepless, Smooth Output

Peak Performance. Unmatched Efficiency.

The Olympus E Star® is built with advanced technology to deliver consistent, powerful heating and cooling without the high energy bill. Its inverter technology automatically adjusts to maintain your desired temperature, eliminating the constant on-and-off cycling of traditional systems. This means you get a more comfortable room, quieter operation, and significantly lower energy costs.



ENERGY SAVINGS

Variable speed technology
Energy Star® certified models



EASY MAINTENANCE & INSTALLATION

Washable filters
No major renovations, patching or painting required



COMFORT IN ANY CLIMATE

Operate in temperatures as low as -22°F and as high as 122°F
Can serve as the primary heat source, eliminating the need for a backup

WHEN WILL YOU NEED AN OLYMPUS MINI SPLIT?



Room Variety

Individual control for different rooms with different comfort settings.



Bedroom

Enhance the comfort in your most used rooms.




New Spaces

Complete climate control for additions without sacrificing other spaces.



Cold & Hot Spots

Perfect for garages and sun rooms.



Features Built for You

Total Climate Control: Enjoy quiet, powerful cooling even in scorching heat and reliable heating in sub-zero temperatures. The Olympus E Star® is designed to thrive in any climate.



Smart & Simple Control: Operate your system from anywhere using the included remote or the MRCOOL® smartphone app. Adjust settings, create schedules, and monitor your system with a tap.



Ultra-Quiet Operation: With indoor noise levels as low as 16 decibels, you'll barely know it's there. It's the perfect solution for bedrooms, home offices, and living areas where quiet is essential.

Ductless Installation: The Olympus E Star® flexible installation is simple for contractors, which saves both time and money for you and them. Ductless installation means no demo, patching or repainting required.

More Great Features



Leakage Detection



Follow Me®




Gold Fin® Condenser



DC Inverter

Compact & Slim Design



Ready to experience comfort on an entirely new level?

The MRCOOL® Olympus E Star® is available now at leading HVAC dealers and online retailers.

SPECIFICATION

OLYMPUS E STAR® SERIES

MODEL NO.	Indoor Unit	0-09-HP-WMAH-230C-0	0-12-HP-WMAH-230C-0	0-18-HP-WMAH-230C-0	0-24-HP-WMAH-230C-0
	Outdoor Unit	0-ES-09-HP-C-230C-01	0-ES-12-HP-C-230C-01	0-ES-18-HP-C-230C-01	0-ES-24-HP-C-230C-01
CAPACITY & PERFORMANCE					
Cooling Capacity	Btu/h	9000	12000	18000	24000
SEER2	Btu/W	27.4	25.4	21.4	21.0
EER2	Btu/W	15.4	13.4	12.5	13.0
Heating Capacity	Btu/h	12000	12000	18000	29000
HSPF2-4	Btu/W	12.5	10.5	11.0	13.5
HSPF2-5	Btu/W	9.5	8.0	8.5	9.8
Indoor air flow (Turbo/Hi/Mi/Lo/Si)	CFM	441.4 / 323.7 / 229.6 / 176.6 / 147.2	441.4 / 323.7 / 229.6 / 176.6 / 147.2	635.7 / 500.3 / 359.0 / 294.3 / 294.3	812.3 / 618.0 / 412.0 / 317.8 / 317.8
Indoor noise level (Turbo/Hi/Mi/Lo/Si)	dB(A)	38 / 38 / 33 / 20.5 / 19.5	47 / 36.5 / 32.5 / 22 / 19.5	49.5 / 45.0 / 38.0 / 31.5 / 19.5	54.5 / 43.5 / 38.5 / 27 / 16
ELECTRICAL PARTS					
Power Supply	V-Hz, Ph	208/230-60, 1	208/230-60, 1	208/230-60, 1	208/230-60, 1
Indoor Minimum Circuit (Disconnect)	A	3.0	3.0	3.0	3.0
Indoor Maximum Fuse (Breaker)	A	15.0	15.0	15.0	15.0
Outdoor Minimum Circuit (Disconnect)	A	15.0	15.0	19.0	24.9
Outdoor Maximum Fuse (Breaker)	A	15.0	15.0	20.0	25.0
DIMENSIONS & WEIGHT					
Net Dimension (WxDxH)	Indoor	inch	33.74 x 9.09 x 11.81	33.74 x 9.09 x 11.81	40.31 x 9.69 x 12.64
	Outdoor	inch	31.69 x 12.99 x 21.81	31.69 x 12.99 x 21.81	35.04 x 13.46 x 26.50
Packing Dimension (WxDxH)	Indoor	inch	36.22 x 12.20 x 14.57	36.22 x 12.20 x 14.57	43.11 x 12.80 x 15.75
	Outdoor	inch	36.02 x 14.57 x 24.21	36.02 x 14.57 x 24.21	39.17 x 15.67 x 29.13
Net Weight	Indoor	lbs	23.37	22.93	27.34
	Outdoor	lbs	72.75	72.75	99.87
Gross Weight	Indoor	lbs	29.98	29.32	36.60
	Outdoor	lbs	78.70	78.70	107.80
REFRIGERANT & PIPING					
Refrigerant R-454B	oz	35.27	35.27	55.38	63.49
Piping Size Liquid Side/Gas Side	inch	1/4"-3/8"	1/4"-3/8"	1/4"-1/2"	3/8"-5/8"
REBATE SUMMARY					
Energy Star V6.1		✓	✓	✓	✓
Energy Star V6.1 Cold Climate		✓	✓	✓	✓
Federal Tax Credits		✓	✓	✓	✓
NEEP		✓	✓	✓	✓
GHG		✓	✓	✓	✓
CEE Tier 1 - North		✓	✓	✓	✓
CEE Tier 2 - North		✓**	✓**	✓**	✓**
CEE Tier 1 - South		✓	✓	✓	✓
CEE Tier 2 - South		✓**	✓**	✓**	✓**
MASS Save		✓	✓	✓	✓



*This system can qualify for the Extended Limited Lifetime Replacement Program only if enrolled in the MRCOOL® Care Kit Program, which has a fee to be covered by the system owner, and certain conditions/requirements are met.

**Not applicable in a ducted installation.

Data Provided by AHRI